

LOZOVA MACHINERY

Price List

21.12.2017

Agricultural Machinery



MONEY WORKS!



DUCAT COMPACT DISC HARROWS

TECHNICAL DATA	DUCAT-2,5	DUCAT-3	DUCAT-4	DUCAT-5	DUCAT-6	DUCAT-8	DUCAT-12	DUCAT-16
Working width, m	2,5	3	4	5,25	6,25	8,25	12,25	16,75
Tractor power, hp	min. 80	min. 100	min. 130	min. 150	min. 170	min. 300	min. 350	min. 450
Coupling with tractor	mounted	mounted	mounted	semi-mounted	semi-mounted	trailed	semi-trailed	trailed
Basic weight, kg	1040	1330	1600	3613	4482	6615	9910	13380
Number of discs	20	24	32	42	50	66	98	134
Disc diameter, mm	566							
Overload protection	3D-protection							
Operating depth, cm	3-12	3-12	3-12	3-14	3-14	3-14	3 - 14	3-14
Operating speed, km/h	10...17	10...17	10...17	10...17	10...17	10...17	10...17	10...17
Efficiency, ha/h	max. 3,09	max. 3,70	max. 4,95	max. 6,49	max. 7,73	max. 10,30	max. 15,29	max. 20,29
Fuel consumption, l/ha	4,5...5,5	4,5...5,5	4,5...5,5	4,5...5,5	4,5...5,5	4,5...5,5	4,5...5,5	4,5...5,5
Transport dimensions (length x width x height), mm	2456x 2691x 1450	2456 x 3000 x 2000	2456x 4190x 1550	5789x 3020x 3210	5780x 3751x 3020	10368x 3960x 2641	8497x 3020x 3636	18944x 3960x 4095

PRICE, € (VAT excluded)

3 776

5 132

7 763

15 461

20 526

31 382

50 658

68 289

PRICE, € (VAT excluded)

ROLLERS

DUCAT-3

DUCAT-5

DUCAT-6

Double U-roller	7 150	20 563	23 853
Rubber roller	7 626	21 385	24 675
Pack ring roller	6 735	20 563	23 853
Crosskill roller	7 204	21 385	24 675



DUCAT GOLD HEAVY DISC HARROWS

TECHNICAL DATA	DUCAT GOLD
Working width, m	8
Tractor power, hp	min 350
Coupling with tractor	trailed
Weight, kg	13 500
Number of disks, pcs.	50
Disc with big diameter, mm	724
Load per disc, kg	260
Heavy tine	spring protection
Operation depth, cm	5 - 20
Operation speed, km/h	10-17
Efficiency, ha/h	max 12
Fuel consumption, l/ha	5 – 7,5
Transport dimensions (length x width x height), mm	7495 x 3970 x 4000

PRICE, € (VAT excluded)

56 711



THALER SYSTEM CARRIER

TECHNICAL DATA	2 pcs. of DUCAT-4	2 pcs. of SHILLING-4
Working width, m	8,25	8
Tractor power, hp	min. 250	min. 450
Coupling with tractor	semi-trailed	semi-trailed
Basic weight, kg	6006	5764
Operating depth, cm	3-12	5...22
Operating speed, km/h	10...17	7...12
Efficiency, ha/h	max. 10,30	max. 7,92
Fuel consumption, l/ha	4,5...5,5	6...15
Transport dimensions (length x width x height), mm	5630x3086x3723	5734x3323x4080

PRICE, € (VAT excluded)

12 763



CHERVONETS SEEDBED CULTIVATORS

TECHNICAL DATA	CHERVONETS-8
Working width, m	8
Tractor power, hp	min. 150
Coupling with tractor	mounted / semi-trailed
Basic weight, kg	2673...3590
Number of tines, pcs	65
Operating depth, cm	3-15
Operating speed, km/h	10...15
Efficiency, ha/h	up to 8,55
Fuel consumption, l/ha	3,5...5,0
Transport dimensions (length x width x height), mm	semi-trailed – 5345x3020x4000.

PRICE, € (VAT excluded)

15 000



DINAR ROTARY HARROW

TECHNICAL DATA	DINAR
Working width, m	6,4
Tractor power, hp	110
Coupling with tractor	trailed
Weight, kg	1700
Number of tines, pcs	36
Number of stars, pcs	72
Number of wheels, pcs	2
Operation depth, cm	max 5
Operation speed, km/h	max 20
Efficiency, ha/h	max 12,8
Transport dimensions (length x width x height), mm	1800 × 3000 × 3800

PRICE, € (VAT excluded)

9 539



FRANC SUBSOILER

TECHNICAL DATA	FRANC
Working width, m	2,5
Tractor power, hp	min. 160
Coupling with tractor	mounted
Basic weight, kg	1490
Number of tines, pcs.	5
Operating depth, cm	up to 45
Operating speed, km/h	8...12
Efficiency, ha/h	max. 2,23
Fuel consumption, l/ha	10...18
Transport dimensions (length x width x height), mm	2860x2479x1885

PRICE, € (VAT excluded)

4 964



GULDEN TWO-LEVEL SUBSOILER

TECHNICAL DATA	GULDEN
Working width, m	4
Tractor power, hp	min. 350
Coupling with tractor	mounted
Basic weight, kg	2678
Number of discs	front row - 7; rear row - 6
Operating depth, cm	front row up to 45 cm; rear row up to 25 cm
Operating speed, km/h	8...12
Efficiency, ha/h	max. 3,58
Fuel consumption, l/ha	10...18
Transport dimensions (length x width x height), mm	4344x4054x2053

PRICE, € (VAT excluded)

11 237



LIRA HYDRAULIC SPRING-TOOTH WIDE LEVEL HARROWS

TECHNICAL DATA	LIRA-15	LIRA-24
Working width, m	15	24
Tractor power, hp	min. 80	min. 130
Coupling with tractor	trailed	trailed
Basic weight, kg	2032	2850
Number of working tools	200	320
Teeth spacing, mm	38	38
Teeth tilt angle, °	15, 30, 45, 60, 75, 90	15, 30, 45, 60, 75, 90
Operating depth, cm	max. 9	max. 9
Operating speed, km/h	8...15	8...15
Efficiency, ha/h	max. 12,1	max. 19,4
Fuel consumption, l/ha	0,8...1,5	0,8...1,5
Transport dimensions (length x width x height), mm	10462x4200x2460	17190x4400x2460
PRICE, € (VAT excluded)	7 000	10 226



REAL UNITS FOR SPREADING OF PLANT PROTECTING AGENTS AND COMPLEX FERTILIZERS

TECHNICAL DATA	REAL-15+LIRA-15	REAL-24+LIRA-24
Working width, m	15	24
Tractor power, hp	min. 80	min. 150
Coupling with tractor	semi-mounted	semi-mounted
Dry weight (excluding the harrow weight), kg	920	2040
Number of nozzles, pcs.	30	48
Tank volume, m ³	2,5	5,0
Pump performance, l/min.	185	250
Distance between nozzles and soil, m	0,5	0,5
Operating speed, km/h	8...12	8...12
Efficiency, ha/h	max. 13,1	max. 21,0
Fuel consumption, l/ha	1,0...1,8	1,0...1,8
Transport dimensions (length x width x height), mm	13876x4200x2460	21600x4400x2460
PRICE, € (VAT excluded)	7 632	11 645



CROWN NO-TILL UNITS

TECHNICAL DATA	CROWN-3,6+SZ-3,6	CROWN-5,4+SZ-5,4
Working width, m	3,6	5,4
Tractor power, hp	min. 80	min. 150
Coupling with tractor	semi-mounted	semi-mounted
Basic weight, kg	1895	2628
Rows number	24	36
Row spacing, cm	15	15
Operating depth, cm	3...8	3...8
Operating speed, km/h	6...12	6...12
Efficiency, ha/h	max. 3,24	max. 4,80
Fuel consumption, l/ha	5,5...7,5	5,5...7,5
Transport dimensions (length x width x height), mm	4764x3732x1800	5612x4353x3000
PRICE, € (VAT excluded)	8 160	11 450



SHILLING INTENSIVE STUBBLE CULTIVATORS

TECHNICAL DATA	SHILLING-2	SHILLING-3	SHILLING-4	SHILLING-6
Working width, m	2,24	3,14	4,0	6,0
Tractor power, hp	min. 80	min. 130	min. 160	min. 300
Coupling with tractor	mounted	mounted	mounted	mounted
Basic weight, kg	748	1340	1480	2906
Number of tines, pcs.	5	7	9	13
Operating depth, cm	5-22	5-22	5-22	5-22
Operating speed, km/h	7...12	7...12	7...12	7...12
Efficiency, ha/h	max. 2,07	max. 3,01	max. 3,96	max. 5,84
Fuel consumption, l/ha	6...15	6...15	6...15	6...15
Transport dimensions (length x width x height), mm	2613x2508 x1450	3427x3410 x1450	2902x4397 x1850	3554x3024 x3900
PRICE, € (VAT excluded)	3 816	5 329	6 974	11 822



UPEC

*UPEC Industrial Group
Agricultural Division*

*UPEC TRADING – official distributor
of LOZOVA MACHINERY*

*4, Marshal Batitskiy Str.
Kharkov, 61038, Ukraine*

*phone.: +38 057 738 10 43
+38 057 738 10 14*

agro@upec-trading.com



**LOZOVA
MACHINERY**

www.lozovamachinery.com